



Order no.: 114060

2-section rope-extension
ladder DIN EN 1147

Number of rungs

2x10

2x11

2x12

2x13

2x14

2x15

2x16

2x17

Specification

Intended use Rettung	Ladder length retracted 3.5 m	Ladder length extended 5.5 m	Setting angle 70 °	Clear width between rungs 270 mm
Clear width, upper ladder 350 mm	Clear width, lower ladder 425 mm	Outer width 490 mm	Ladder feet Stahlspitze	Depth of side-rails 74 mm
Width of side-rails 35 mm	Step/Rung height 28 mm	Step depth 29 mm	Number of steps/rungs 2x 10 rungs	Max. load capacity 324 kg
Persons max. 3	Material Aluminium	Rung covering Standard (rot)	Business division MUNK Rettungstechnik	Order no. 114060

Facts

- 2-section rope-extension ladder made of aluminium
- Rescue ladder compliant with DIN EN 1147
- With heat-insulating, non-slip and secure-grip plastic coating
- With rope pulley, locking hook and rope brake

- 4-fold edged rung-to-side-rail connection
- Corrosion-resistant fixtures made of galvanised steel
- Lower ladder with steel spikes at the base
- Upper ladder with wall wheels
- Non-slip and replaceable ladder shoes
- Permissible load: 324 kg / 3 people

More product pictures



Corporate certifications

Standards for quality and sustainability

