



Order no.: 071050

Telescopic ladder for
climbing onto vehicles,
with retractable hooks



Specification

Step design Sprossen	Outer width 375 mm	Width of side-rails 25 mm	Number of steps/rungs 6 rungs	Step depth 30 mm
Transport dimensions (plus packaging) 1907 x 375 x 105 mm, 10.9 kg	Business division MUNK Günzburger Steigtechnik	Order no. 071050		

Facts

- Aluminium telescopic rung ladder
- Integrated mounting hooks grip securely onto the vehicle body – for safe access to tippers, vans and commercial vehicles
- Stable rectangular tube side-rails
- Rectangular rungs grooved on both sides, 30 x 30 mm, Slip resistance class R10
- Extends from 1,900 mm to 3,309 mm – can be locked in place at each rung to accommodate vehicles of different heights

- Specially designed for boarding tippers, vans and commercial vehicle bodies – whether on everyday construction sites or in haulage operations
- High-strength rung-to-side-rail connection
- Rung distance: 280 mm
- Maximum load: 150 kg
- Note: In accordance with TRBS 2121 Part 2, a suitable accessory is required for working on this ladder

Scope of supply

- Ladder: 1 x
- Instructions for use and operation: 1 x

More product pictures



Added value

Industrial grade

Stable and robust for tough everyday working life (including 4-way edging)

- Corrosion-resistant fixtures
- Use of high-quality and high-strength materials
- Versatile and practical accessories



Large range of accessories

- The right equipment for every application
- Practical and makes work easier
- Suitable for universal use on Günzburger Steigtechnik ladders



Corporate certifications

Standards for quality and sustainability

