

Order no.: 125111

FlexxTower SG



Platform height [mm]

- 2100
- 3100
- 4100



Specification

Working height 6.1 m	Scaffolding height 5.3 m	Platform height 4.1 m	Platform width 600 mm	Platform length 1.2 m
Load capacity 2 kN/m2	Weight 130 kg	Transport dimensions 1650 x 800 x 1860 mm, 130 kg	Business division MUNK Günzburger Steigtechnik	Article no. 125111
Price € 5,000.00				

Facts

- Mobile scaffolding made of sturdy aluminium tubing with welded frame parts
- For lower workplaces, the scaffolding can also be assembled at lower heights
- Secured on all sides thanks to leading railing; can be assembled and dismantled from level to level by one person (can be used by up to two people)
- Tool-free assembly thanks to push-fit connectors and quick-release connectors
- Easy to handle thanks to individual lightweight parts

- Space-saving transport and storage, as individual parts can be stacked compactly into each other and used as a trolley
- Excellent flexibility and stability, thanks to fold-out triangular outrigger with swivel base – also ideal for wall mounting or moving in narrow passages
- Four Ø 125 mm swivel castors with centric load application and spindles
- Aluminium toe boards and powder-coated railing frames with integrated knee rail as a safety railing
- GS-tested as per DIN EN 1004
- Load class/scaffolding group 3: 2.0 kN/m²

Scope of supply

- | | |
|--|---|
| ■ FlexxTower push-fit frame: 10 x | ■ FlexxTower platform with trapdoor: 2 x |
| ■ FlexxTower triangular outrigger: 4 x | ■ FlexxTower swivel castor Ø 125 mm: 4 x |
| ■ FlexxTower toe board, long side: 2 x | ■ FlexxTower double railing: 2 x |
| ■ FlexxTower toe board, front: 2 x | ■ Instructions for assembly and use EN 1004-2 - de: 1 x |
| ■ Components, accessories and spare parts: 4 x | |

Information on sustainability criteria

- Corporate certification: ISO 9001
- Corporate certification: EN 1090
- Corporate certification: EcoVadis
- RoHS
- REACH
- The MUNK Group complies with a Code of Conduct
- The Supply Chain Act does not apply due to our size
- The materials used are listed in the technical specification
- Resource-saving production: own photovoltaic systems
- Energy-efficient consumption during production: LED lighting
- Repairability, durability and quality: 15-year warranty on series products made in Germany
- Recyclability: Our products are mostly made of aluminium, steel or wood and can be fed directly into the recycling process.

- Socially acceptable working conditions in production: fair wages, gender equality
- Economical and recyclable packaging: no use of polystyrene, predominantly use of wood and cardboard, small amounts of plastic
- No health hazards for the users

More product pictures



Added value

Safety at heights

- Optional protective assembly railing as safety railing during installation and removal
- Installation without the need of tools, uncomplicated and easy to handle
- Railing with integrated knee board and aluminium toe boards



Modular kit system

- More than 180 variants are possible by combining different individual parts
- Flexible adaptations and extensions possible at any time
- Individual parts at the original part price
- Installation and removal without tools



Highest quality

- User-friendly and robust design
- Low weight of the individual parts for easy handling
- Welded round tube frames for maximum stability
- All-round profiled rungs for safe ascent and descent



Sturdy connection

- Automatically closing scaffolding claw with sophisticated geometry for a secure connection
- Innovative spring clip for plug-on frame – no accidental loosening or losing possible
- Transverse and diagonal braces for high stability



Flexible basis

- Swivel castors with load centring in braked condition
- Height adjustment for level compensation
- Various sizes and designs



Accessories

Safe standing

- Adjustable outriggers with swing base or chassis bar ensure safe working depending on model
- Easy to handle
- Additional ballast weights required depending on application



Everything at a glance

- Clip tray for clearly visible attachment of the necessary test documents to the scaffolding
- Weather and UV-resistant





Order no.: 012909

FlexxTower stairway kit
1



Order no.: 012910

FlexxTower stairway kit
2



Order no.: 012956

Components,
accessories and spare
parts



Order no.: 012905

FlexxTower push-fit
frame



Order no.: 012943

FlexxTower toe board,
long side



Order no.: 012913

FlexxTower toe board,
front



Order no.: 012926

FlexxTower triangular
outrigger



Order no.: 012973

FlexxTower swivel
castor Ø 125 mm



Order no.: 012908

FlexxTower spindle
foot



Order no.: 012931

FlexxTower platform
with trapdoor



Order no.: 019081

Clip tray for tubes



Order no.: 070506

Frame extension can
be clamped on



Order no.: 027912

Ballast weight



Order no.: 019274

Storage tray 500 x 220
mm



Order no.: 019276

Storage tray 800 x 300
mm



Order no.: 019176
Inventory sticker



Order no.: 019175
Inspection sticker

Spare parts



Order no.: 012956
Components,
accessories and spare
parts



Order no.: 012905
FlexxTower push-fit
frame



Order no.: 012926
FlexxTower triangular
outrigger



Order no.: 012973
FlexxTower swivel
castor Ø 125 mm



Order no.: 012931
FlexxTower platform
with trapdoor

Corporate certifications

on sustainability criteria

